
TABLE OF CONTENTS

1.0 SCOPE AND PURPOSE	1
1.1 SCOPE	1
1.2 PURPOSE	1
1.3 EQUIVALENCY OF WAFER OR DIE LEVEL RESULTS.....	1
2.0 REFERENCED PUBLICATIONS	1
3.0 DEFINITIONS	1
4.0 APPARATUS AND REQUIRED EQUIPMENT	4
4.1 WAVEFORM VERIFICATION EQUIPMENT	4
4.1.1 Oscilloscope.....	4
4.1.2 Current Probe.....	4
4.1.3 Evaluation Loads.....	4
4.1.4 Attenuator.....	5
4.2 HUMAN BODY MODEL SIMULATOR	5
4.2.1 HBM Test Equipment Parasitic Properties	6
5.0 STRESS TEST EQUIPMENT QUALIFICATION AND ROUTINE VERIFICATION	6
5.1 OVERVIEW OF REQUIRED HBM TESTER EVALUATIONS	6
5.2 MEASUREMENT PROCEDURES	6
5.2.1 Reference Pin Pair Determination	6
5.2.2 Waveform Capture with Current Probe.....	6
5.2.3 Determination of Waveform Parameters.....	7
5.2.4 High-Voltage Discharge Path Test.....	10
5.3 HBM TESTER QUALIFICATION.....	10
5.3.1 HBM Tester Qualification Procedure	10
5.4 TEST FIXTURE BOARD QUALIFICATION FOR SOCKETED TESTERS	11
5.5 ROUTINE WAVEFORM CHECK REQUIREMENTS.....	12
5.5.1 Standard Routine Waveform Check Description	12
5.5.2 Alternate Routine Waveform Capture Procedure	13
5.6 HIGH-VOLTAGE DISCHARGE PATH CHECK.....	13
5.6.1 Relay Testers	13
5.6.2 Non-Relay Testers	13
5.7 TESTER WAVEFORM RECORDS.....	14
5.7.1 Tester and Test Fixture Board Qualification Records.....	14
5.7.2 Periodic Waveform Check Records	14
5.8 SAFETY	14
5.8.1 Initial Set-Up.....	14
5.8.2 Training	14
5.8.3 Personnel Safety.....	14
6.0 CLASSIFICATION PROCEDURE	14

6.1	PARAMETRIC AND FUNCTIONAL TESTING	15
6.1.1	<i>Handling Devices</i>	15
6.2	DEVICE STRESSING.....	15
6.2.1	<i>No-Connect Pins</i>	15
6.3	PIN COMBINATION STRESSING.....	16
6.3.1	<i>“No-Connect” Pins</i>	16
6.3.2	<i>Supply Pins</i>	16
6.3.3	<i>Non-Supply Pins</i>	17
6.4	PIN GROUPINGS	17
6.4.1	<i>Supply Pin Groups</i>	17
6.4.2	<i>Shorted Non-Supply Pin Groups</i>	18
6.5	PIN STRESS COMBINATIONS	18
6.5.1	<i>Non-Supply and Supply to Supply Combinations (1, 2, ...N)</i>	20
6.5.2	<i>Non-Supply to Non-Supply Combination</i>	22
6.6	PIN-PAIR STRESSING	22
6.7	LOW-PARASITIC HBM SIMULATOR ALLOWANCE	22
6.8	TESTING AFTER STRESSING	22
7.0	FAILURE CRITERIA	22
8.0	DEVICE CLASSIFICATION	23
Annexes		
Annex A (Normative):	Cloned Non-Supply (IO) Pin Sampling Test Method	24
Annex B (Normative):	Determination of Withstand Thresholds for Pin or Pin-Combination Subsets	30
Annex C (Informative):	HBM Test Equipment Parasitic Properties	32
Annex D (Informative):	HBM Test Method Flow Chart	38
Annex E (Informative):	Failure Window Detection Testing Methods	41
Annex F (Informative):	Bibliography	43
Annex G (Informative):	Revision History for ANSI/ESDA/JEDEC JS-001	44
Figures		
Figure 1:	Simplified HBM Simulator Circuit with Loads	5
Figure 2A:	Current Waveform Through a Shorting Load ($I_{ps_{max}}$)	8
Figure 2B:	Current Waveform Through a Shorting Load (t_d).....	8
Figure 3:	Current Waveform Through a 500-Ohm Resistor	9
Figure 4:	Peak Current Short-Circuit Ringing Waveform	9
Figure 5:	SPL, V1, VM, and z with the Bell Shape Distribution Pin Failure Curve	25
Figure 6:	IO Sampling Test Method Flow Chart	29
Figure 7:	Diagram of Trailing Pulse Measurement Setup	32
Figure 8:	Positive Stress at 4000 Volts	32
Figure 9:	Negative Stress at 4000 Volts	33
Figure 10:	Illustrates Measuring Voltage Before HBM Pulse With a Zener Diode or a Device....	34
Figure 11:	Example of Voltage Rise Before the HBM Current Pulse Across a 9.4-Volt Zener Diode	34

Figure 12: Optional Pre-Current Pulse Detection Equipment/Apparatus	35
Figure 13: Positive Stress at 1000 Volts	35
Figure 14: Diagram of a 10-Pin Shorting Test Device Showing Current Probe	37
Figure 15: Test Equipment Qualification and Verification.....	38
Figure 16: HBM Classification Procedure	39
Figure 17: Pin Categorization and Groupings	40

Tables

Table 1: Waveform Specification.....	12
Table 2A: Required Pin Combination Sets.....	19
Table 2B: Legacy Pin Combination Sets.....	20
Table 3: HBM ESD Device Classification Levels	23
Table 4: Inclusion of Lower ESD Level High-Speed Pin Data	31